



BRILL® Mixed Viscosity Table

12.5W-40 × 20W-60

12.5W-40	20W-60	Viscosity(40°C)	Viscosity(100°C)	Mixed Viscosity Grade
100%	0%	88.3	13.4	12.5W-40
95%	5%	91.6	13.8	12.5W-40
90%	10%	95.1	14.2	12.5W-40
85%	15%	98.6	14.7	12.5W-45
80%	20%	102.3	15.1	15W-45
75%	25%	106.1	15.6	15W-45
70%	30%	110.1	16.0	15W-45
65%	35%	114.1	16.5	17.5W-45
60%	40%	118.4	17.0	17.5W-50
55%	45%	122.7	17.5	17.5W-50
50%	50%	127.3	18.1	17.5W-50
45%	55%	132.0	18.6	20W-50
40%	60%	136.8	19.2	20W-50
35%	65%	141.8	19.7	20W-55
30%	70%	147.0	20.3	20W-55
25%	75%	152.4	20.9	20W-55
20%	80%	157.9	21.6	20W-55
15%	85%	163.7	22.2	20W-55
10%	90%	169.6	22.9	20W-60
5%	95%	175.8	23.6	20W-60
0%	100%	182.1	24.3	20W-60

Unit for Viscosity mm²/S